



### **150L COOLED INCUBATOR**

Model: 354







# **FEATURES**

- The unit is ideal for use in cultivating low temperature microbes and plant cells, general pharmacy, clinical science and biology
- Electronic P.I.D temperature control with digital indication of set and process value
- High accuracy PT 100 temperature sensor
- Solid state control relay for optimum reliability and rapid response
- Reliable refrigeration system with high quality compressor and components
- Grade 304 stainless steel interior

- Temperature range -10°C to +60°C @25°C Ambient
- Fully adjustable shelf heights
- Forced air circulation for excellent temperature uniformity
- High quality silicon door seal to minimise heat loss
- Uses 134a Refrigerant
- Automatic defrost function
- Temperature Variation across chamber +1°∩

### NOTE

- Supplied with 2 chrome plated wire shelves
- Optional inner glass viewing door for sample inspection without affecting chamber temperature





### 150L COOLED INCUBATOR

Model: 354

## **SPECIFICATIONS**

POWER
VOLTAGE
PACKAGING (W x D x H)
UNIT (W x D x H)
NET WEIGHT
GROSS WEIGHT
SHIPPING VOLUME
CCHAMBER DIMENSIONS
CHAMBER VOLUME
SHELF CAPACITY

1100W 230V / 50Hz 800 x 810 x 1090 (mm) 685 x 755 x 890 (mm) 82kg 90kg 0.71m<sup>3</sup> 595 x 495 x 495 (mm)


150 l 7 with 50mm Spaces


### **OPTIONAL EXTRAS**


CODE	DESCRIPTION
361	Extra chrome plated wire shelf
359	Inner glass door

### NOTE

Perforated trays available on request







### NOTE

• When viewing the appliance from the front in it's usual operating position, the width (W) of the product is the total distance from left to right; the depth (D) of the product is the total distance from the front to the back; the height (H) is the total distance from the bottom of the product to the top. Pictures may vary from actual product.

### **DISCLAIMER**

• Output performance figures quoted are dependant on various factors. Scientific reserves the right, without notice, to make changes and revisions to product specifications, materials and design, when we believe it will provide better performance, durability, and efficiency. Unit measurements may vary depending on point of reference.

### WARRANTY

• All Scientific equipment comes with a standard ONE year warranty, The 1 Year Extended Warranty is only valid for customers who have registered their warranty online at www.scientific.co.za within the first year after making their purchase.



www.scientific.co.za

**Published Date**: 2020.09.25