



400L COOLED INCUBATOR

Model: 356







FEATURES

- The unit is ideal for use in cultivating low temperature microbes and plant cells, general pharmacy, clinical science and biology
- Electronic P.I.D temperature control with digital indication of set and process value
- High accuracy PT 100 temperature sensor
- Solid state control relay for optimum reliability and rapid response
- Reliable refrigeration system with high quality compressor and components
- Grade 304 stainless steel interior

- Temperature range 0°C to +60°C @25°C Ambient
- Fully adjustable shelf heights
- Forced air circulation for excellent temperature uniformity
- High quality silicon door seal to minimise heat loss
- Automatic defrost function
- Temperature Variation across chamber +1°C
- Uses 404 refrigerant

NOTE

- Supplied with 4 chrome plated wire shelves
- Optional inner glass viewing door for sample inspection without affecting chamber temperature





400L COOLED INCUBATOR

Model: 356

SPECIFICATIONS

 POWER
 1200W

 VOLTAGE
 230V / 50Hz

 PACKAGING (W x D x H)
 760 x 880 x 19

PACKAGING (W x D x H) 760 x 880 x 1960 (mm)
UNIT (W x D x H) 685 x 810 x 1820 (mm)

NET WEIGHT 100kg GROSS WEIGHT 104kg SHIPPING VOLUME 1.31m³


CHAMBER DIMENSIONS 595 x 495 x 1305 (mm)

CHAMBER VOLUME 400ℓ


SHELF CAPACITY 21 with 50mm spacing

OPTIONAL EXTRAS

CODE	DESCRIPTION
361A	Extra chrome plated wire shelf
360	Inner glass door







NOTE

• When viewing the appliance from the front in it's usual operating position, the width (W) of the product is the total distance from left to right; the depth (D) of the product is the total distance from the front to the back; the height (H) is the total distance from the bottom of the product to the top. Pictures may vary from actual product.

DISCLAIMER

• Output performance figures quoted are dependant on various factors. Scientific reserves the right, without notice, to make changes and revisions to product specifications, materials and design, when we believe it will provide better performance, durability, and efficiency. Unit measurements may vary depending on point of reference.

WARRANTY

• All Scientific equipment comes with a standard ONE year warranty, The 1 Year Extended Warranty is only valid for customers who have registered their warranty online at www.scientific.co.za within the first year after making their purchase.



www.scientific.co.za

Published Date: 2020.09.25