



## **400L VERTICAL - ECONOMY INCUBATOR**

Model: 229V







# **FEATURES**

- Scientific general purpose incubators are ideal for use in the fields of life science, pharmacy, clinical science, chemistry and biology
- Grade 304 S/S interior
- Bodies are constructed from corrosion protected mild steel with an epoxy powder coated finish
- Sized to fit through a standard width door frame
- Ideal for applications where a lower degree of accuracy is acceptable

- Hydraulic thermostat control
- Operating temperature +37°C to 110°C based on an ambient of 25°C
- Temperature variation across chamber ±1.5°C
- Fitted with adjustable hydraulic safety thermostat

### NOTE

- Temperature variation figures are based on no load conditions at 37°C
- Supplied with 2 chrome plated steel wire shelves





### **400L VERTICAL - ECONOMY INCUBATOR**

Model: 229V

## **SPECIFICATIONS**


**POWER** 1500W **VOLTAGE** 230V / 50Hz PACKAGING (W x D x H) 940 x 850 x 1520 (mm) UNIT (W x D x H) 735 x 795 x 1325 (mm) **NET WEIGHT GROSS WEIGHT** 120kg SHIPPING VOLUME 1.21m<sup>3</sup> **CHAMBER DIMENSIONS** 620 x 570 x 985 (mm) **CHAMBER VOLUME** 4008 SHELF CAPACITY MAXIMUM SHELF LOAD 20kg (per shelf)


### **OPTIONAL EXTRAS**


CODE	DESCRIPTION
213	Chrome plated wire shelf
218	Perforated stainless steel shelf
252	24hr timer
253	Inlet fan for rapid drying
254	Timer run down facility
255	Fan speed reducer
244V	Inner glass door

### NOTE

Special drying trays, racking systems, programmable controllers and process recorders are available on request







### NOTE

• When viewing the appliance from the front in it's usual operating position, the width (W) of the product is the total distance from left to right; the depth (D) of the product is the total distance from the front to the back; the height (H) is the total distance from the bottom of the product to the top. Pictures may vary from actual product.

### **DISCLAIMER**

• Output performance figures quoted are dependent on various factors. Scientific reserves the right, without notice, to make changes and revisions to product specifications, materials and design, when we believe it will provide better performance, durability, and efficiency. Unit measurements may vary depending on point of reference.

### WARRANTY

• All Scientific equipment comes with a standard ONE year warranty, The 1 Year Extended Warranty is only valid for customers who have registered their warranty online at www.scientific.co.za within the first year after making their purchase.



www.scientific.co.za

**Published Date: 2020.09.25**